Oceanus-36 Single Colour LED Spot Lights

Product Code: OC36-SC



Key Features

- Vandal-resistant 8mm tempered glass front
- Powered by ProLight Opto LED's
- Water Resistant to IP66
- Tough & durable powder coated diecast aluminium housing

Product Description

The Oceanus-36 LED Spotlight is a single colour flood/spotlight which is fully water and dust resistant to IP66 rating, making the Oceanus-36 LED Spotlight at home in any indoor or outdoor venue.

The fully adjustable and lockable bracket ensures easy mounting on most surfaces.

Available in various colour combinations the Oceanus-36 LED Spotlight can create any mood or effect you desire. External DMX decoders and LED controllers are available.

Specification

Lighting Performance

| LED Qty | Lumen Output | CRI | Minimum Lifetime |
|-----------|--------------|-----|------------------|
| 36 x PM2B | 4500lm | >80 | 30,000hrs |

Operating Details

| Input Power | Working Temperature Range |
|-------------|---------------------------|
| 50W | -15 to +50 °C |

Input Data

| Input Voltage | Power Supply Type | Input Connection |
|---------------|------------------------|------------------|
| 24V DC | Constant Voltage Drive | Flying Leads |

Options

| | Optics | LED Colour |
|---|--------------------------|------------|
| 15°, 25°, 45°, 60°, 120° Red, Green, Blue, Amber, Warm White, Neutral White, Pure White | 15°, 25°, 45°, 60°, 120° | |

Physical Details

| Mounting Type | Finish | Ingress Protection |
|---|---|--------------------|
| Bracket mounting for walls/floors/ceilings | Black powder coated with stainless steel bezel | IP66 |

Colour

